

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1 1. (previously presented) A system, comprising:
2 a backplane having a plurality of conductors;
3 a first plurality of printed circuit boards plugged into the backplane, each one of the
4 first printed circuit boards having a plurality of electrical contacts, each one of the electrical
5 contacts providing an indication of an incapability of an electrical component on such one of
6 the printed circuit boards, each one of such electrical contacts of the first plurality of printed
7 circuit boards being electrically connected together through a corresponding one of the
8 plurality of conductors of the backplane;
9 circuitry connected to the plurality of conductors for converting the operating
10 incapability indications provided by the plurality of printed circuit boards into logic signals
11 on the plurality of conductors;
12 a second plurality of printed circuit boards plugged into the backplane, each one of
13 the second plurality of printed circuit boards having a decoder responsive to the logic signals
14 on the plurality of conductors for selecting an operating characteristic for electrical
15 components on the second plurality of printed circuit boards, such selected operating
16 characteristic being compatible with operating characteristics of the electrical components on
17 the first plurality of printed circuit boards.

1 2. (original) The system recited in claim 1 wherein the operating characteristic is operating
2 speed and wherein the decoders select the highest speed compatible with the speed
3 capability of the electrical components on the plurality of first printed circuit boards.

1 3. (previously presented) A system, comprising:
2 a backplane having a plurality of conductors;

3 a first plurality of printed circuit boards plugged into the backplane, each one of the
4 first printed circuit boards having a plurality of electrical contacts, each one of the electrical
5 contacts providing an indication signal representative of a predetermined operating
6 incapability of an electrical component on such one of the printed circuit boards, each one of
7 such electrical contacts of the first plurality of printed circuit boards being electrically
8 connected together through a corresponding one of the plurality of conductors of the
9 backplane;

10 a second plurality of printed circuit boards plugged into the backplane, each one of
11 the second plurality of printed circuit boards having a decoder responsive to the incapability
12 indication signal on the plurality of conductors for selecting an operating characteristic for
13 electrical components on the second plurality of printed circuit boards, such selected
14 operating characteristic being compatible with operating characteristics of the electrical
15 components on the first plurality of printed circuit boards.

1 4. (original) The system recited in claim 3 wherein the operating characteristic is operating
2 speed and wherein the decoders select the highest speed compatible with the speed
3 capability of the electrical components on the plurality of first printed circuit boards.

1 5. (previously presented) A system, comprising:

2 a backplane having a plurality of conductors;

3 a first plurality of printed circuit boards plugged into the backplane, each one of the
4 first printed circuit boards having a plurality of electrical contacts, each one of the electrical
5 contacts providing an indication of a predetermined speed incapability of an electrical
6 component on such one of the printed circuit boards, each one of such electrical contacts of
7 the first plurality of printed circuit boards being electrically connected together through a
8 corresponding one of the plurality of conductors of the backplane;

9 circuitry connected to the plurality of conductors for converting the operating speed
10 incapability indications provided by the plurality of printed circuit boards into logic signals
11 for the plurality of printed circuit boards;

12 a second plurality of printed circuit boards plugged into the backplane, each one of
13 the second plurality of printed circuit boards having:

14 an electrical component; and
15 a source of a plurality of clock signals, each one of the plurality of clock
16 signals having a different rate;
17 a decoder for coupling one of the plurality of clock signals to the electrical
18 component on such one of the second plurality of printed circuit boards selectively in
19 accordance with the provided logic signals; and
20 wherein the decoders of the second plurality of printed circuit boards couple to
21 the electrical components thereon the one of the plurality of clock signals having a
22 rate compatible with operating speeds of the electrical components on the first
23 plurality of printed circuit boards.

1 6. (original) The system recited in claim 5 wherein the circuitry provides a wired-NOR
2 configuration.

1 7. (original) The system recited in claim 5 wherein each one of the plurality of contacts is
2 connected to ground potential when such contact provides an indication of operating
3 speed incapability; otherwise such contact is open circuited.

1 8. (original) The system recited in claim 7 wherein the circuitry provides a wired-NOR
2 configuration.

1 9. (original) The system recited in claim 5 wherein the decoders select as the rate a rate
2 compatible with operating speeds of the electrical components on the first plurality of
3 printed circuit boards the one of the plurality of clock signals having the highest rate
4 compatible with the speed capability of the electrical components on the plurality of first
5 printed circuit boards.

1 10. (previously presented) A system, comprising:
2 a backplane having a plurality of conductors;
3 a plurality of resistors, each one connected between a corresponding one of the
4 plurality of conductors and a voltage source;

5 a first plurality of printed circuit boards plugged into the backplane, each one of the
6 first printed circuit boards having a plurality of electrical contacts, each one of the electrical
7 contacts of the first plurality of printed circuit boards being connected to a corresponding one
8 of the plurality of conductors, each one of such contacts being connected to either ground or
9 to an open circuit, connection to ground providing an indication of an operating speed
10 incapability of an electrical component on such one of the first printed circuit boards;

11 wherein the contact connected to ground provides a first logic state on the one of the
12 plurality of conductors connected thereto when such contact is connected to ground and
13 provides a second logic state on the one of the plurality of conductors connected thereto when
14 such contact is connected to an open circuit;

15 a second plurality of printed circuit boards plugged into the backplane, each one
16 thereof having:

17 an electrical component; and

18 a source of a plurality of clock signals, each one of the plurality of clock
19 signals having a different rate;

20 a decoder for coupling one of the plurality of clock signals to the electrical
21 component on such one of the second plurality of printed circuit boards selectively in
22 accordance with the provided logic states; and

23 wherein the decoders of the second plurality of printed circuit boards couple to
24 the electrical components thereon the one of the plurality of clock signals having a
25 rate compatible with operating speeds of the electrical components on the first
26 plurality of printed circuit boards.

1 11. (original) The system recited in claim 10 wherein the decoders selects as the rate a rate
2 compatible with operating speeds of the electrical components on the first plurality of
3 printed circuit boards the one of the plurality of clock signals having the highest rate
4 compatible with the speed capability of the electrical components on the plurality of first
5 printed circuit boards.

1 12. (previously presented) A system comprising:
2 a backplane having a plurality of conductors;

3 a plurality of printed circuit boards plugged into the backplane, each one of the
4 printed circuit boards having a plurality of electrical contacts, each one of the electrical
5 contacts providing an indication of a predetermined operating incapability of an electrical
6 component on such one of the printed circuit boards, each one of such electrical contacts of
7 the plurality of printed circuit boards being electrically connected together through a
8 corresponding one of the plurality of conductors of the backplane;

9 circuitry connected to the plurality of conductors for converting the operating
10 incapability indications provided by the plurality of printed circuit boards into logic signals
11 for the plurality of printed circuit boards.

1 13. (original) The system recited in claim 12 wherein the operating incapability is operating
2 speed.

1 Cancel claim 14.

1 Cancel claim 15.

1 Cancel claim 16.

1 Cancel claim 17.

1 18. (currently amended) A method for operating a system, comprising:

2 providing a backplane system comprising:

3 a plurality of printed circuit ~~boards~~ boards each one having an electrical
4 component thereon; and

5 a backplane having plugged therein the plurality of printed circuit boards
6 for producing a signal indicative of a speed compatibility of the electrical
7 components;

8 plugging an additional printed circuit ~~board~~ board having an electrical component
9 thereon into the provided backplane, the electrical component on such additional printed

10 circuit board being incompatible with the speed of the electrical components on the plurality
11 of printed circuit boards;

12 an electrical circuit for electrically inhibiting the electrical coupling of the electrical
13 component on the additional printed circuit board from the electrical components of the
14 plurality of printed circuit boards.

1 19. (previously presented) A method comprising:

2 providing a backplane having a plurality of conductors with a plurality of printed
3 circuit boards plugged into the backplane, each one of the printed circuit boards having a
4 plurality of electrical contacts, each one of the electrical contacts providing an indication of a
5 predetermined operating incapability of an electrical component on such one of the printed
6 circuit boards, each one of such electrical contacts of the plurality of printed circuit boards
7 being electrically connected together through a corresponding one of the plurality of
8 conductors of the backplane; and

9 converting the operating incapability indications provided by the plurality of printed
10 circuit boards into logic signals for the plurality of printed circuit boards.

1 20. (original) The method recited in claim 19 wherein the operating incompatibility is
2 operating speed.

21. (original) The method recited in claim 19 wherein the operating incompatibility is operating protocol.